

	Page 1 of 1		DRAWN 09.04.2021 BY RKT	
	CABLE REQUIREMENTS:	PLUG / END A REQUIREMENTS:	CONNECTOR / END B REQUIREMENTS:	
	Colour: BLACK	Type: FREE END	Type: SG597D	
AK5281	Type:3 Core 1.00mm² H05VV-F (European Approved)	Colour: N/A	Colour: BLACK	
ANJZOI	Neutral (Blue)	Rating: N/A	Rating: 10A	
PC2056	Live (Brown	Reference:	Reference: D/A C13 IEC Lock+ Connector	
	Complete Powerlead Rated: 10A/250V		(European Approved)	
Free End Overall Strip Lengths (Includes Terminations) Live = 50mm (+/- 5mm) Neutral = 50mm (+/- 5mm) Live = 50mm (+/- 5mm) Earth = 50mm (+/- 5mm)			bownwards Angle 90 degrees	
	909m	m (+/-15mm)	→ 	
	1000m	ım (+/-15mm)		

CHANGE MANAGEMENT:	HANKING	APPROVAL DETAILS:		
		LIVE / BROWN	NEUTRAL / BLUE	EARTH / GREEN & YELL
		Type: Stripped	Type: Stripped	Type: Stripped
	Fig.8			
	(200mm)	Size: 6mm	Size: 6mm	Size: 6mm
	x <i>y</i>			
			l	1
	CHANGE MANAGEMENT:	Fig.8	Fig.8	LIVE / BROWN NEUTRAL / BLUE Fig.8 Type: Stripped Type: Stripped