

SCALE 1/1

Specification :

Adaptor	Type	Color
MTP	SC Footprint A Type(Up to Down)	Black
LC	Zirconia	Violet

	Type
Direct Harness(12C)	OM4, 0.9mm Jacket, PVC, MTP+Guide Pin, LC UPC, Low Loss

LC	Straight Version	MTP
1	←→	1
2	←→	2
3	←→	3
4	←→	4
5	←→	5
6	←→	6
7	←→	7
8	←→	8
9	←→	9
10	←→	10
11	←→	11
12	←→	12

LC Fiber Number	Jacket Color	Fiber Position	MTP Fiber Number
Fiber 1	Blue	B	Fiber 1
Fiber 2	Orange	A	Fiber 2
Fiber 3	Green	B	Fiber 3
Fiber 4	Brown	A	Fiber 4
Fiber 5	Gray	B	Fiber 5
Fiber 6	White	A	Fiber 6
Fiber 7	Red	B	Fiber 7
Fiber 8	Black	A	Fiber 8
Fiber 9	Yellow	B	Fiber 9
Fiber 10	Purple	A	Fiber 10
Fiber 11	Pink	B	Fiber 11
Fiber 12	Aqua	A	Fiber 12

- a. Dimension: 1.36" x 3.46" x 4.33"
(34.5 x 88.0 x 110.0mm)
- b. Weight: 0.25kg.
- c. Surface Finished: Painted, BK(RAL9005)


GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.1 X.XX ±0.2 X.X ±0.3	DRAWING	24.JUL.2023	DANIEL	ACT	
	CHECK	24.JUL.2023	DAY		
	APPROVAL	24.JUL.2023	FRANK		
	DATE	NAME	ITEM NO.: FA2054		
	SCALE	1/2(A4)	UNIT	mm	DES.:CASSETTE 1MTP-12DLC OM4 HD
HSF Spec.		DRAWING NO. CASSETTE 1MTP-12DLC OM4 HD(SA1)			
RoHS		DRAWING CLASSIFICATION	S SHEET		1 OF 2

1 2 3 4 5 6

30.0cm^{+0.0cm}_{-2.0cm}

A

A



B


B

Specification :

- Material :
1. Connector Type : MTP Male(With Pin) Connector, Multimode Low Loss.
 - 1-1. Protective Cap : TPR, Black color.
 - 1-2. MT Ferrule : 12 Fibers, PPS, Black color, Multimode Low Loss.
 - 1-3. MTP Housing : PBT, Aqua color.
 2. Connector Type : LC Multimode Low Loss, Ivory Color.
 - 2-1. Protective Cap : PE, White color.
 - 2-2. Ferrule : $\phi 1.25\text{mm}$, Zirconia, Singlemode.
 - 2-3. LC Housing : PC, Ivory color.
 - 2-4. Strain Relief Boot : PVC, White color.
 3. Shrink Tube : 1.5cm. Use Black Heat Shrink Tube.
 4. Tubing Type:
 - 4-1. Fiber : OM4 50/125um Multimode.
 - 4-2. 12 tubes Hytel material, 0.9mm tube of 12 Colors.
 5. Fanout MTP(Male) to LC OM4 12C Patch cord 30cm.
 - 1(Blue)/2(Orange)/3(Green)/4(Brown)/5(Gray)/6(White)/7(Red)/8(Black)/9(Yellow)/10(Purple)/11(Pink)/12(Aqua).

C

C



- Performance :
- a. Insertion Loss :
 - LC MM Low Loss : < 0.15dB
 - MTP MM Low Loss : < 0.35dB
 - b. Return Loss :
 - LC MM Low Loss : > 35 dB
 - MTP MM Low Loss : > 20 dB
 - c. Fiber Extention(LC) : $-0.05\mu\text{m} < H < +0.05\mu\text{m}$
 - d. Fiber overcut(MTP) : 1~3um
 - e. Apex Offset : < 50um
 - f. Operating Temperature : -20°C to $+70^{\circ}\text{C}$
 - g. Storage Temperature : -40°C to $+80^{\circ}\text{C}$

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.1 X.XX ±0.2 X.X ±0.3	DRAWING	24.JUL.2023	DANIEL	ACT	
	CHECK	24.JUL.2023	DAY		
	APPROVAL	24.JUL.2023	FRANK		
	DATE		NAME		ITEM NO.: FA2054
SCALE	1/4 (A4)	UNIT	mm	DES.: CASSETTE 1MTP-12DLC OM4 HD	
HSF Spec.			DRAWING NO.	CASSETTE 1MTP-12DLC OM4 HD(SA1)	
RoHS			DRAWING CLASSIFICATION	S	

D

2 0 3 4 10cm 5 6