



ITEM	PART	DESCRIPTION
A + B	Connector type	HDMI A male with shielding shell (tinplate)
	Contacts	Gold plated
	Hood	Molded plastic
	Shield type	Aluminum Mylar
	Conductor material	Copper
C	Cable colour	Black
	Outer jacket	PVC
	Wire gauge	26 AWG
	Outer diameter	Ø8.0 ±0.15mm
	Bend radius	40mm
	Temperature range	-20°C to +70°C (+5%)
	Humidity range	45% to 65%
	Max. bandwidth	18 Gb/s
	HDMI version	2.0
	HDMI standard	HDMI High Speed premium certified
	Ethernet support	Yes
	Max. resolution @ 30Hz	3840 x 2160 (4K)
	Max. resolution @ 60Hz	3840 x 2160 (4K)
	Chroma sampling	4:4:4
	Colour bit depth	8 bits per colour

HDMI High Speed premium certified cable v2.0 HDMI-A male - HDMI-A male

Item : AK3946	Revision : 01-AA
Date : 29-09-2023	

This drawing is proprietary information of ACT Connectivity Solutions and confidential and provided to you for internal use on a need to know basis only. This document may not be duplicated for or disseminated to any third party without the prior explicit written consent of ACT Connectivity Solutions. Copies of this document, Printed or electronic, are uncontrolled and intended only for immediate use.

Drawn by : EP