

Product Code: STF076 PA135015BK6

Description: C13 IEC Locking 6 Tier Appliance Outlet



General Information

| | |
|------------------------------|--|
| Rating | 10A Max / 250V~ (Europe) 15A Max / 250V~ (cUL) |
| Materials | Face & Back Cover: Polyamide 66 (PA66) - To RAL Colour 9004 (Signal Black) Gloss Finish Contacts: Tin Plated Copper Alloy (CuSn5 PB102 1/2 Hard Phosphor Bronze) Push Button: Polycarbonate - To RAL Colour 3020 (Traffic Red) Spring: Steel (Zinc Plated, Clear Passivate and de-embrittle) Locking Tab: Manganese Steel 65Mn (Zinc Plated to EN 1706) 5 Microns Spring: Spring Steel Locking Blade: Spring Steel Zinc Plated Red Handle: Polycarbonate (RAL 3020 Traffic Light Red) |
| Panel Thickness | 1.5mm |
| Aperture Cutout | (32.4-32.8mm) x (174.5-174.7mm) |
| Receptacle Size | 6.3mm x 0.8mm |
| Insulation Resistance | 100MΩ (500V DC, 1 Min) |
| Dielectric Strength | 2KV (50Hz 1Min) to accessible surfaces |
| Temperature Rating | -20°C To + 70°C |
| Lock Retention | > 100N |
| Features | Fits any standard C14 connector Anti-Vibrate Integral plug retention feature Easy push button to release |
| Standards | IEC /BS EN 60320-1:2015 (DEKRA File NL-45977) IEC /BS EN 60320-3:2014 (DEKRA File NL-45977) UL 60320-1 (UL Fie E348985) UL 60320-3 (UL Fie E348985) |