



PART NO.	Length
RL3100	0,5 mtr
RL3100	1 mtr
RL3151	1,5 mtr
RL3102	2 mtr
RL3152	2,5 mtr
RL3103	3 mtr
RL3105	5 mtr
RL3107	7 mtr
RL3110.	10 mtr

PIN LAYOUT		Description	Fiber	ITEM	PART NO.	DESCRIPTION	QTY/MTR									
Conector		Cable Color	Yellow	1	..	E2000Male Connector APC8°	1									
A		Category	OS2	2	..	E2000 Male Connector APC8°	1									
B		Fiber Diameter	9/125μ	3	..	SC Male Connector UPC	1									
		Type Fiber Cable	Patch Cord Duplex	4	..	SC Male Connector UPC	1									
		Category	G.657A1	5	..	OS2 G.657A1 Fiber Duplex	XX mtr									
		Min. operating temperature	-20	..	..	..	..									
		Max. operating temperature	+60	..	..	..	..									
		Jacket	LSZH	..	..	..	..									
		Insertion Loss	Average <0.12dB, Max. ≤0.25dB	..	..	..	..									
STATUS:	<b>Final</b>	Return Loss	APC ≤65dB, UPC ≤55dB					TITLE: <b>E2000/APC8° - SC/UPC 9/125 OS2 duplex patchcable</b>								
SIGNED:		OD	2.00 mm						DRAWN BY:	Gerard van Eede	DRAW DATE	20-01-2020	REVISED	10-4-2020	REV	1.00
									PROJECT NR:		XXXXX-XXXX	PAGE		1 / 1		

ACT  
 DRAWN BY: Gerard van Eede  
 Unless otherwise specified: Dimensions are in millimeters