


PACKING:

ROUND CABLE METHOD SEE "DETAIL A"

	BAG TYPE	QTY	LABEL
SMALL	POLYBAG	1 CABLE WITH TEST CARD	SEE "DETAIL B"



DETAIL B
y: Year; mm: Month
xxxxx: Serial Number

ASSEMBLY CONNECTIVITY	
Side:A- LC/UPC	Side:B- SC/UPC
A	B
B	A

RL8001

LC/UPC-SC/UPC duplex patchcord OM1 1M


IIC: 04015001-P0015774

ACT is a registered trademark. All mentioned brand names are registered trademarks of their respective owners. Rights to the registered Names / Logos / Trademarks / Brands / Service Marks featured are property of and belong to their respective owners. Developed and styled in Europe, made in China. Misprints and errors reserved. ACT cannot be held liable or responsible for inaccurately presented content. ACT, Kooihoovenstraat 1E, 3722 MT Barneveld, The Netherlands.

We advice to clean all the connector ferrules for optimal performance. You can find safety information at www.act-connectivity.com/safety


www.act-connectivity.com

DETAIL C



DETAIL A

RoHS Complaint



Partnumber	Length	Tolerance	Partnumber	Length	Tolerance
RL8000	0.5M	0/+100mm	RL8005	5M	0/+100mm
RL8001	1M	0/+100mm	RL8010	10M	0/+100mm
RL8051	1.5M	0/+100mm	RL8015	15M	0/+100mm
RL8002	2M	0/+100mm	RL8020	20M	0/+100mm
RL8003	3M	0/+100mm	RL8030	30M	0/+150mm

LC/UPC --- SC/UPC duplex (1.9±0.1)*(4.0±0.2)mm OM1 LSZH Orange		
ITEM	Description	Q'TY
1	LC dust cover white	2 PCS
2	LC/UPC MM duplex connector beige	1 PC
3	LC clip beige	1 PC
4	LC short boot white L=19.5±0.5mm	1 PC
5	LC short boot yellow L=19.5±0.5mm	1 PC
6	LC heat-shrink tube white	1 PC
7	LC heat-shrink tube yellow	1 PC
8	Breakout heat-shrink tube black L=15mm	2 PCS
9	Cable lable	1 PC
10	OD=(1.9±0.1)*(4.0±0.2)mm duplex OM1 fiber optical cable LSZH Orange	1 PC
11	SC boot black	1 PC
12	SC boot red	1 PC
13	SC clip beige	1 PC
14	SC/UPC MM simplex connector beige	2 PCS
15	SC dust cover lucency	2 PCS

ACT			
Designed by:		Audit:	
Date:	2021-06-23	Approve:	
Unit:	mm	Sheet:	A4
Drawing NO:	RL80xx LC/UPC-SC/UPC duplex patchcord OM1-V1		



Product Specification

Standard Compliances

1. ANSI/TIA-568.3-D.
2. ISO 11801 OM1 /IEC60793-2-10 type A1a.
3. Telcordia GR-326-CORE Issue 4 February 2010 Compliance.
4. RoHS Compliance for the Requirement of European Union Issued Directive 2011/6S/EU.

Construction&Characteristics

Optical Performance	Insertion loss typical	0.15dB
	Insertion loss maximum	0.25dB
	Return loss	≥30dB
	Polish	UPC
Connector	Connector A side	IEC61754-20 LC connector
	Connector B side	IEC61754-4 SC connector
	Ferrule	Ceramic Zirconia (ZrO2)
Cable	Fiber class	OM1
	Fiber type	Multimode 62.5/125
	Cable type	(1.9±0.1)*(4.0±0.2)mm LSZH Orange
	Tensile strength	200N (short time 400N)
	Operation temp.	-20 °Cto +80 °C (5 cycles)
	Vibration	10 to 55 Hz 15mm double amplitude
Marking	ACT Premium Multimode Fiber Optic Patch cable 62.5/125µm,OM1,LSZH xxxM	

100% tested and approved

1. ACT advices to clean every connector ferrule before usage to get optimal performance.
2. Always leave the dust caps on if the cable isn't installed.